

Technical drawing of a rectangular plate with dimensions and a grid of holes. The overall dimensions are 640 (width) and 255 (height). The plate has a thickness of 4. A grid of 12 holes is shown, arranged in 3 rows and 4 columns. The holes are labeled with a diameter of $\phi 17.5$. The center-to-center distance between adjacent holes is 107.5. The distance from the left edge to the first column of holes is 107.5. The distance from the top edge to the first row of holes is 107.5. The distance between the first and last columns of holes is 4x150 (=600). A dimension line labeled '1' indicates the distance from the top edge to the first row of holes.

نام شرکت:	مهندسی و ساختمان ماشین سازی اراک
نام پروژه:	ساخت و نصب سیمان گگن
نمونه کننده:	م. ا. عیان
تاریخ:	۱۳۸۱/۰۲/۲۲

Paßnaß	Abnaße

96	Dat.	Name		Oberflächenbeschaffenheit nach ISO 1302 Mittenrauhwert Ra (µm)															
Gez.	23.8.	H. Ho																	
Gepr.	29.9	Qui				-		-	-	-	-	-	-	-	-	-	-	-	-
Gen.	13.10.	FR				Index	Planquadrat/Änderungsgrund				Datum	Gez.	Gepr.	Gen.					
POLYSIUS A NORMUNG nach ISO 2768-mK DIN Grad Allgemeintoleranzen für Gußteile für Schweiß- konstruktionen nach ISO 13920 KL. F. Längen KL. F. Winkel				Gewicht: (kg)		232.74.41 -				Erz.		No.							
				Rohteil-Nr.:		551.639				Index		Zeichnungs-Nr.							
				Abnahmeöße mit Maßkontrolle															
Maßstab in Original 1:5				Benennung: Abdeckplatte Typ: 1000 Schotterschlt.						Blattzahl: 1 Blatt: 1 Format A 4									
										Ersatz für:									
 KRUPP POLYSIUS 										Ersetzt durch:									
										Entstanden aus:									